

|    |   | North              | South              | East               | West               |
|----|---|--------------------|--------------------|--------------------|--------------------|
| 1. | Total Façade S.F.                               | XX s.f.            | XX s.f.            | XX s.f.            | XX s.f.            |
| 2. | Façade S.F.<br>(exclusive of doors and windows) | XX s.f.            | XX s.f.            | XX s.f.            | XX s.f.            |
| 3. | Doors and Windows S.F.                          | XX s.f.            | XX s.f.            | XX s.f.            | XX s.f.            |
| 4. | <b>Primary Masonry totals<br/>(Min. 80%)</b>    | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 |
|    | • Brick s.f.<br>(as applicable)                 | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 |
|    | • Stone s.f.<br>(as applicable)                 | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 |
|    | • *Stucco s.f.<br>(as applicable)               | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 |
|    | • Tilt Wall s.f.<br>(as applicable)             | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 |
| 5. | <b>Secondary Masonry totals<br/>(max. 20%)</b>  | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 |
|    | • EIFS s.f.<br>(as applicable)                  | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 |
|    | • Hardiplank s.f.<br>(as applicable)            | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 |
|    | • Detail any additional<br>(as applicable)      | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 | XX s.f. and % of 2 |

**\*NOTE:** Per paragraph 5.3 of the Urban Design Plan, the maximum percentage of stucco allowed on any building elevation shall be 80%. If the entire 80% primary masonry on a building elevation consists of stucco, then the remaining 20% on the same building elevation shall be limited to hand-laid brick or stone.